

**Dimensions**

Length (Overall): 131 Ft  
 Beam (Overall): 77 Ft  
 Hull Depth (Overall): 10 Ft  
 Open Deck Area: 3,500 Sq Ft

**Hull Characteristics**

Gross Tonnage: Under 200 GT  
 International: Under 1,600 GT  
 Max. Deck Cargo: 300 Kips  
 Hull Material: Steel

**Regulatory Classification**

ABS Loadline Only, /MARPOL,  
 USCG Subchapter L

**Legs**

Number: 3  
 Length: 175 Ft w/o pads  
 Type: Pipe  
 : 52 in Diameter x 1 1/2  
 in Wall Thickness  
 Material: High Strength 70 KSI  
 Steel

**Pads**

Length: 28 Ft  
 Width: 13 Ft

**Cranes**

Number: 2  
 Primary Crane: 100 ton Hyd Operated  
 Crane Engine: Cummins  
 Auxiliary Crane: 25 ton  
 Crane Engine: Cummins 6CTA 8.3M  
 Cranes  
 Certifications: API Spec RP2C

**Propulsion**

Main Engines: (2) Cummins KTA 38-  
 MO/  
 850 BHP ea.  
 PTO: (2) Driving Hyd  
 Pumps  
 Reduction Gears: (2) Twin Disc

**Emergency Generator**

Generator Drive: Cummins 6BT  
 Generator: 90 kW, 460 VAC,  
 3PH, 60 Hz

**Capacities**

Fuel: 10,300 Gallons  
 Fresh Water: 17,000 Gallons  
 Lube Oil: 250 Gallons  
 Hydraulic Oil: 1,000 Gallons  
 Dirty Oil: 250 Gallons  
 Oily Bilge Water: 250 Gallons  
 Zero Discharge Tank: 1,750 Gallons

**Accommodations**

Staterooms: 9  
 Berths: 36  
 Laundry: 2/2 W/D  
 Sanitary Facilities: (6) Waterclosets

**Galley/Mess Area**

Number of Seats: 16  
 Equipment List:  
 Range, Deep Fryer, 2ea.Ref/Frz, Steam Table,  
 Milk Dispenser, Ice Machine, Water Dispenser,  
 Griddle

**Navigation Equipment**

Radar, Depth Sounder, Loudhailer, GMDSS  
 Station, Mag Compass, Wind Speed and  
 Direction, (2) VHF Radios, SSB, GPS,  
 Autopilot

**Life Saving Equipment**

Life Rafts: (6) 12 Man  
 Rescue Boat with Motor and Davit

**Jacking**

Max Working Water  
 Depth: 130 Ft  
 Wave Height: 5 Ft  
 Total Variable Load: 550 Kips  
 Jacking Speed: Under Load 4-5 FPM  
 Air Gap: 15 Ft

**Speed**